




## HLM 43135

### High-Power Synchronous Servo Motors - slim design -


Motor series HLM 43135  
peak torque 22 Nm  
with brushless pancake-resolver




#### Operation characteristics:

Measured at servo-amplifier with 3-phase sinusoidal output


HLM 43135, 320V, 3000/5000rpm




HLM 43135, 320V, 3000/7000rpm



HLM 43135, 560V, 3000/5000rpm



HLM 43135, 560V, 3000/7000rpm



#### Motor design:

The High-Power Synchronous Servo Motors of series HLM 43135 are fitted with a 3-phase concentrated stator-winding system. The 6-pole rotor-magnet system is made of high-grade Neodymium Iron Boron.

The motors have a sinusoidal Back EMF.

The position information of the rotor, a required tacho voltage and pulses for a closed loop position control will be generated using the integrated brushless pancake-resolver. To avoid thermal overload a PTC resistor is embedded in the stator winding.

#### Features:

- High acceleration because of small moments of inertia

- Large peak torques because of high allowable pulse currents
- Increased maximum speed because of reduced no-load losses
- Decreased cogging effects achieved by system improvement
- Maintenance-free operation due to brushless design - mechanical life cycle only depends on bearing and its lubrication
- High overload range due to high thermal time constant and good dissipation of the power-losses occurred in the stator
- The extremely slim design allowing excellent peak torque capabilities in a motor housing with very small diameter
- Sinusoidal Back EMF

edition 06.17

type series		HLM 43135		HLM 43135			
max. speed	rpm	5000	-	7000	-		
bus voltage	V	320	560	320	560		
nominal speed	rpm	3000	3000	3000	3000		
nominal current <sup>1) **)</sup>	A	7,9	4,1	11	5,8		
nominal power <sup>2)</sup>	W	1100	1070	1005	1005		
operation acc. to standards VDE 0530		S1		S1			
protection acc. to standards VDE 0530		IP 54		IP 54			
rotating direction		reversible		reversible			
structural shape acc. standards VDE 0530		B 14		B 14			
kind of connection		connectors (see below)		connectors (see below)			
<b>mechanical data:</b>							
moment of inertia motor	kgm <sup>2</sup>	0,26*10 <sup>-3</sup>					
moment of inertia resolver	kgm <sup>2</sup>	0,0025*10 <sup>-3</sup>					
nominal torque <sup>2)</sup>	Nm	3,5	3,4	3,2	3,2		
max. continuous torque at stall <sup>2)</sup>	Nm	4,5	4,4	4,2	4,2		
peak torque	Nm	25	25	25	25		
max. time to peak torque <sup>2) 6)</sup>	s	10	10	10	10		
speed regulation constant	N <sup>-1</sup> cm <sup>-1</sup> rpm	0,34	0,36	0,34	0,35		
mechanical time constant	ms	1,1	1,1	1,1	1,1		
friction torque	Nm	0,15					
rotor weight motor	kg	1,6					
rotor weight resolver	kg	0,04					
motor weight incl. resolver	kg	6,6					
ball bearings	A/B-side	6202/6201					
F <sub>R</sub> (allowable radial shaft load) <sup>3)</sup>	N	200					
F <sub>A</sub> (allowable axial shaft load)	N	80					
<b>electrical data:</b>							
number of phases		3					
number of poles		6					
terminal resistance <sup>4)</sup>	Ω	0,88	3,3	0,38	1,4		
inductance <sup>4)</sup>	mH	3,4	12	1,5	5,2		
voltage constant <sup>1) *</sup>	V/1000 rpm	56	105	37	70		
torque constant <sup>1) *</sup>	Nm/A	0,463	0,868	0,306	0,579		
current at peak torque <sup>1) **)</sup>	A	62,5	33	94,5	50		
max. peak current <sup>1) 5)</sup>	A	75	40	115	60		
electrical time constant	ms	3,9	3,6	3,9	3,7		
<b>thermical data:</b>							
max. ambient temperature	°C	40					
isolation acc. to standards VDE 0530		F					
thermal time constant	min	35		35			
temperature-rise n.v.	K/W	0,7		0,7			
<b>connectors:</b>							
motor flange socket		BEGA 120 NN 00 00 0200 000 (INTERCONTEC)					
resolver flange socket		AEGA 113 NN 00 00 0201 000 (INTERCONTEC)					

<sup>\*)</sup> Tolerance - 10 %

<sup>\*\*)</sup> Tolerance + 10 %

<sup>1)</sup> Sinusoidal-peak

<sup>2)</sup> Values are for motor-assembling on a locating face of aluminium of at least 0,15 m<sup>2</sup> at a thickness of 10 mm or similar metal face.

<sup>3)</sup> Middle of the shaft-extension.

<sup>4)</sup> Measured between two phases.

<sup>5)</sup> The mentioned values are valid for operation in temperature-ranges from 0 up to +40 °C and it is not allowed to exceed them, not even for a short-time, to avoid magnet-weakening.

<sup>6)</sup> Only valid for a once cycle out of could status.

design-changes reserved